(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 19 May 2005 (19.05.2005)

PCT

(10) International Publication Number WO 2005/044380 A1

(51) International Patent Classification⁷:

A62B 1/20

(21) International Application Number:

PCT/GB2004/004607

(22) International Filing Date:

1 November 2004 (01.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0325394.5

30 October 2003 (30.10.2003) GB

- (71) Applicant (for all designated States except US): LATCH-WAYS PLC [GB/GB]; Hopton Park, Devizes, Wiltshire SN10 2JP (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BISSETT, Timothy, George [GB/GB]; Latchways plc, Hopton Park, Devizes, Wiltshire SN10 2JP (GB).
- (74) Agent: REES, Alexander, Ellison; Urquhart-Dykes & Lord, 30 Welbeck Street, London W1G 8ER (GB).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A FALL ARREST SYSTEM



(57) Abstract: A fall arrest system is formed by a vertical cable extending between an upper anchor point and a lower anchor point and a fall arrest device arranged for movement along the cable. An energy absorbing means is associated with the upper anchor point to reduce the forces applied to the anchor point when a fall is arrested.